

PDF technical sheet

7910UADG/GNP42U3G




High precision angular contact ball bearings

High precision angular contact ball bearing, moulded polyamide cage centred on balls


Product definition

d	1.9685 "
D	2.8346 "
B	0.4724 "
d1	2.2520 "
d2	2.1772 "
D1	2.5551 "
D2	2.6969 "
a	0.7992 "
Contact angle, α	25 °
rs min	0.0236 "
r1s min	0.0118 "
f0	16.3
Precision class	P42
Mass	0.46 oz
Brand	NTN



Product performance

Dynamic load, C	17.90 kN
Static load, C0	15.80 kN
Nlim (oil)	26,900 RPM
Nlim (grease)	16,600 RPM
Preload level	GN
Peload value	177 kN
axial rigidity	138.4 N/ μ m
radial rigidity	293.8 N/ μ m
Min operating temperature, Tmin	-4 °C
Max operating temperature, Tmax	248 °C
Characteristic cage frequency, FTF	0.45 Hz
Characteristic rolling element frequency, BSF	8.45 Hz
Characteristic outer ring frequency, BPF0	9.39 Hz
Characteristic inner ring frequency, BPFI	11.61 Hz



Abutment dimensions

da min	2.1457 "
Da max	2.6575 "
Db max	2.7362 "
r1a max	0.0118 "
ra max	0.0236 "
D6	2.2559 "

Calculation factors

Equivalent dynamic radial load

$$P = X.F_r + Y.F_a$$

Series			e	Single or DT bearing arrangement				DB or DF arrangement			
				Fa / Fr ≤ e		Fa / Fr > e		Fa / Fr ≤ e		Fa / Fr > e	
				X	Y	X	Y	X	Y	X	Y
70 (NTN & SNR) 72 (NTN & SNR) 78 (NTN) 79 (NTN) 719 (SNR)	15°	0.178	0.38	1	0	0.44	1.47	1	1.65	0.72	2.39
		0.357	0.4				1.4		1.57		2.28
		0.714	0.43				1.3		1.46		2.11
		1.07	0.46				1.23		1.38		2
		1.43	0.47				1.19		1.34		1.93
		2.14	0.5				1.12		1.26		1.82
		3.57	0.55				1.02		1.14		1.66
		5.35	0.56						1.12		1.63
		7.14	0.56				1		1.12		1.63
	25°		0.68	1	0	0.41	0.87	1	0.92	0.67	1.41
	30°		0.8								0.78

Equivalent static radial load

$$P_o = X_o.F_r + Y_o.F_a$$

Series			Single or DT bearing arrangement		DB or DF arrangement	
			X ₀	Y ₀	X ₀	Y ₀
70 (NTN & SNR) 72 (NTN & SNR) 78 (NTN) 79 (NTN) 719 (SNR)	15°		0.5	0.46	1	0.92
	25°			0.38		0.76
	30°			0.33		0.66

For single or DT bearing arrangement :

If $P_o < F_r$, then use $P_o = F_r$