

PDF technical sheet 7036HVUJ74



High precision angular contact ball bearings

High precision angular contact ball bearing, laminated resin cage centred on outer ring

Product definition	
d	7.0866 "
D	11.0236 "
B	1.8110 "
d1	8.3425 "
D1	9.7686 "
D2	10.3774 "
a	3.0315 "
Contact angle, α	25 °
rs min	0.0827 "
r1s min	0.0433 "
f0	15.942
Precision class	P4
Mass	31.75 oz
Brand	SNR



Product performance	
Dynamic load, C	228 kN
Static load, C0	276 kN
Fatigue limit load, Cu	10.20 kN
Nlim (oil)	7,000 RPM
Nlim (grease)	4,600 RPM
Axial displacement K Factor	0.35
Preload level	7
Peloid value	3,100 kN
axial rigidity	594 N/ μ m
radial rigidity	1,255 N/ μ m
Min operating temperature, Tmin	-22 °C
Max operating temperature, Tmax	248 °C
Characteristic cage frequency, FTF	0.44 Hz
Characteristic rolling element frequency, BSF	7.52 Hz
Characteristic outer ring frequency, BPF0	9.25 Hz
Characteristic inner ring frequency, BPF1	11.75 Hz



Abutment dimensions

da min	7.5591 "
db min	7.5591 "
Da max	10.5512 "
Db max	10.5512 "
r1a max	0.0394 "
ra max	0.0787 "
D6	8.6535 "

Calculation factors

Equivalent dynamic radial load

$$P = X \cdot Fr + Y \cdot Fa$$

Series			e	Single or DT bearing arrangement				DB or DF arrangement			
				Fa / Fr ≤ e		Fa / Fr > e		Fa / Fr ≤ e		Fa / Fr > e	
				X	Y	X	Y	X	Y	X	Y
70 (NTN & SNR) 72 (NTN & SNR) 78 (NTN) 79 (NTN) 719 (SNR)	15°	0.178	0.38	1	0	0.44	1.47	1	1.65	0.72	2.39
		0.357	0.4				1.4		1.57		2.28
		0.714	0.43				1.3		1.46		2.11
		1.07	0.46				1.23		1.38		2
		1.43	0.47				1.19		1.34		1.93
		2.14	0.5				1.12		1.26		1.82
		3.57	0.55				1.02		1.14		1.66
		5.35	0.56						1.12		1.63
		7.14	0.56				1		1.12		1.63
	25°		0.68			0.41	0.87		0.92	0.67	1.41
	30°		0.8			0.39	0.76		0.78	0.63	1.24

Equivalent static radial load

$$Po = Xo \cdot Fr + Yo \cdot Fa$$

Series			Single or DT bearing arrangement		DB or DF arrangement	
			X ₀	Y ₀	X ₀	Y ₀
70 (NTN & SNR) 72 (NTN & SNR) 78 (NTN) 79 (NTN) 719 (SNR)	15°		0.5	0.46	1	0.92
	25°			0.38		0.76
	30°			0.33		0.66

For single or DT bearing arrangement :

If $Po < Fr$, then use $Po = Fr$