

PDF technical sheet 6040L1C4



Single row deep groove ball bearings

Deep groove ball bearing, radial contact, machined cage, open


Product definition

d	7.8740 "
D	12.2047 "
B	2.0079 "
rs min	0.0827 "
Radial clearance class	C4
Mass	41.98 oz
Brand	NTN



Product performance

Dynamic load, C	218 kN
Static load, C0	243 kN
Fatigue limit load, Cu	6.90 kN
f0	15.6
Nlim (oil)	2,400 RPM
Nlim (grease)	2,000 RPM
Min operating temperature, Tmin	-76 °C
Characteristic cage frequency, FTF	0.44 Hz
Characteristic rolling element frequency, BSF	7.52 Hz
Characteristic outer ring frequency, BPF0	6.09 Hz
Characteristic inner ring frequency, BPF1	7.92 Hz



Abutment dimensions

da min	8.3071 "
Da max	11.7717 "
ra max	0.0787 "

Calculation factors

Equivalent dynamic radial load

$$P = X.F_r + Y.F_a$$

$\frac{f_0 F_a}{C_0}$	e	$F_a / F_r \leq e$		$F_a / F_r > e$	
		X	Y	X	Y
0.172	0.19	1	0	0.56	2.3
0.345	0.22				1.99
0.689	0.26				1.71
1.03	0.28				1.55
1.38	0.3				1.45
2.07	0.34				1.31
3.45	0.38				1.15
5.17	0.42				1.04
6.89	0.44				1

Equivalent static radial load

$$P_0 = X_0.F_r + Y_0.F_a$$

X_0	Y_0
0.6	0.5

For single or DT bearing arrangement :

If $P_0 < F_r$, then use $P_0 = F_r$