


PDF technical sheet 6316ZC3




Single row deep groove ball bearings

Deep groove ball bearing, radial contact, pressed steel cage, shield on one side


Product definition

d	3.1496 "
D	6.6929 "
B	1.5354 "
rs min	0.0827 "
Radial clearance class	C3
Mass	12.66 oz
Brand	NTN



Product performance

Dynamic load, C	123 kN
Static load, C0	86.50 kN
Fatigue limit load, Cu	3.50 kN
f0	13.3
Nlim (oil)	4,700 RPM
Nlim (grease)	4,000 RPM
Min operating temperature, Tmin	-76 °C
Characteristic cage frequency, FTF	0.39 Hz
Characteristic rolling element frequency, BSF	4.15 Hz
Characteristic outer ring frequency, BPF0	3.09 Hz
Characteristic inner ring frequency, BPF1	4.91 Hz



Abutment dimensions

da min	3.5827 "
Da max	6.2598 "
ra max	0.0787 "

Calculation factors

Equivalent dynamic radial load

$$P = X.F_r + Y.F_a$$

$\frac{f_0 F_a}{C_0}$	e	$F_a / F_r \leq e$		$F_a / F_r > e$	
		X	Y	X	Y
0.172	0.19	1	0	0.56	2.3
0.345	0.22				1.99
0.689	0.26				1.71
1.03	0.28				1.55
1.38	0.3				1.45
2.07	0.34				1.31
3.45	0.38				1.15
5.17	0.42				1.04
6.89	0.44				1

Equivalent static radial load

$$P_0 = X_0.F_r + Y_0.F_a$$

X_0	Y_0
0.6	0.5

For single or DT bearing arrangement :

If $P_0 < F_r$, then use $P_0 = F_r$