

PDF technical sheet 6344L1C3



Single row deep groove ball bearings

Deep groove ball bearing, radial contact, machined cage, open


Product definition

d	8.6614 "
D	18.1102 "
B	3.4646 "
rs min	0.1969 "
Radial clearance class	C3
Mass	214.47 oz
Brand	NTN



Product performance

Dynamic load, C	410 kN
Static load, C0	520 kN
Fatigue limit load, Cu	23.60 kN
f0	14.3
Nlim (oil)	1,600 RPM
Nlim (grease)	1,400 RPM
Min operating temperature, Tmin	-4 °C
Max operating temperature, Tmax	248 °C
Characteristic cage frequency, FTF	0.41 Hz
Characteristic rolling element frequency, BSF	5.17 Hz
Characteristic outer ring frequency, BPF0	3.66 Hz
Characteristic inner ring frequency, BPF1	5.34 Hz



Abutment dimensions

da min	9.4488 "
Da max	17.3228 "
ra max	0.1575 "

Calculation factors

Equivalent dynamic radial load

$$P = X.F_r + Y.F_a$$

$\frac{f_0 F_a}{C_0}$	e	$F_a / F_r \leq e$		$F_a / F_r > e$	
		X	Y	X	Y
0.172	0.19	1	0	0.56	2.3
0.345	0.22				1.99
0.689	0.26				1.71
1.03	0.28				1.55
1.38	0.3				1.45
2.07	0.34				1.31
3.45	0.38				1.15
5.17	0.42				1.04
6.89	0.44				1

Equivalent static radial load

$$P_0 = X_0.F_r + Y_0.F_a$$

X_0	Y_0
0.6	0.5

For single or DT bearing arrangement :

If $P_0 < F_r$, then use $P_0 = F_r$