

PDF technical sheet

6824L1AC4




Single row deep groove ball bearings

Deep groove ball bearing, radial contact, machined cage, open


Product definition

d	4.7244 "
D	5.9055 "
B	0.6299 "
rs min	0.0394 "
Radial clearance class	C4
Mass	1.96 oz
Brand	NTN



Product performance

Dynamic load, C	28.90 kN
Static load, C0	33 kN
Fatigue limit load, Cu	1.29 kN
f0	16
Nlim (oil)	4,700 RPM
Nlim (grease)	4,000 RPM
Min operating temperature, Tmin	-76 °C
Characteristic cage frequency, FTF	0.47 Hz
Characteristic rolling element frequency, BSF	15.40 Hz
Characteristic outer ring frequency, BPF0	12.63 Hz
Characteristic inner ring frequency, BPF1	14.37 Hz



Abutment dimensions

da min	4.9213 "
Da max	5.7087 "
ra max	0.0394 "

Calculation factors

Equivalent dynamic radial load

$$P = X.F_r + Y.F_a$$

$\frac{f_0 F_a}{C_0}$	e	$F_a / F_r \leq e$		$F_a / F_r > e$	
		X	Y	X	Y
0.172	0.19	1	0	0.56	2.3
0.345	0.22				1.99
0.689	0.26				1.71
1.03	0.28				1.55
1.38	0.3				1.45
2.07	0.34				1.31
3.45	0.38				1.15
5.17	0.42				1.04
6.89	0.44				1

Equivalent static radial load

$$P_0 = X_0.F_r + Y_0.F_a$$

X_0	Y_0
0.6	0.5

For single or DT bearing arrangement :

If $P_0 < F_r$, then use $P_0 = F_r$