

PDF technical sheet 6936L1A



Single row deep groove ball bearings

Deep groove ball bearing, radial contact, machined cage, open

Product definition

d	7.0866 "
D	9.8425 "
B	1.2992 "
rs min	0.0787 "
Radial clearance class	CN
Mass	16.79 oz
Brand	NTN



Product performance

Dynamic load, C	110 kN
Static load, C0	119 kN
Fatigue limit load, Cu	3.70 kN
f0	16.5
Nlim (oil)	2,900 RPM
Nlim (grease)	2,400 RPM
Min operating temperature, Tmin	-4 °C
Max operating temperature, Tmax	248 °C
Characteristic cage frequency, FTF	0.45 Hz
Characteristic rolling element frequency, BSF	10.32 Hz
Characteristic outer ring frequency, BPF0	7.68 Hz
Characteristic inner ring frequency, BPFI	9.32 Hz



Abutment dimensions

da min	7.4409 "
Da max	9.4882 "
ra max	0.0787 "

Calculation factors

Equivalent dynamic radial load

$$P = X.F_r + Y.F_a$$

$\frac{f_0 F_a}{C_0}$	e	$F_a / F_r \leq e$		$F_a / F_r > e$	
		X	Y	X	Y
0.172	0.19	1	0	0.56	2.3
0.345	0.22				1.99
0.689	0.26				1.71
1.03	0.28				1.55
1.38	0.3				1.45
2.07	0.34				1.31
3.45	0.38				1.15
5.17	0.42				1.04
6.89	0.44				1

Equivalent static radial load

$$P_0 = X_0.F_r + Y_0.F_a$$

X_0	Y_0
0.6	0.5

For single or DT bearing arrangement :

If $P_0 < F_r$, then use $P_0 = F_r$