PDF technical sheet
6022C3

Single row deep groove ball bearings
Deep groove ball bearing, radial contact, pressed steel cage, open

Product definition	
d	4.3307 "
D	6.6929 "
B	1.1024 "
d1	4.8701 "
D1	6.1929 "
rs min	0.0787 "
Radial clearance class	C3
Mass	5.26 oz
Brand	SNR



Product performance	
Dynamic load, C	81 kN
Static load, C0	73 kN
Fatigue limit load, Cu	2.80 kN
f0	15.7
Nref	4,800 RPM
Nlim	6,300 RPM
Min operating temperature, Tmin	−40 °C
Max operating temperature, Tmax	248 °C
Characteristic cage frequency, FTF	0.44 Hz
Characteristic rolling element frequency, BSF	7.54 Hz
Characteristic outer ring frequency, BPF0	6.09 Hz
Characteristic inner ring frequency, BPFI	7.91 Hz



NTN-SNR ROULEMENTS – www.ntn-snr.com
1 rue des Usines – 74010 Annecy Cedex – France – Tel. +33 (0)4 50 65 30 00
S.A. au capital de 123 599 542 € - RCS ANNECY B 325 821 072 – Id. Fiscale : FR 48 325 821 072 – SIRET 325 821 072 00015 –
Code APE 2815 Z – Code NACE 28.15

Abutment dimensions	
da min	4.6850 "
Da max	6.3386 "
ra max	0.0787 "

Calculation factors

Equivalent dynamic radial load

P = X.Fr + Y.Fa

$\frac{f_0 F_a}{C_0}$	e	Fa / Fr ≤ e		Fa / Fr > e	
		X	Y	X	Y
0.172	0.19	1	0	0.56	2.3
0.345	0.22				1.99
0.689	0.26				1.71
1.03	0.28				1.55
1.38	0.3				1.45
2.07	0.34				1.31
3.45	0.38				1.15
5.17	0.42				1.04
6.89	0.44				1

Equivalent static radial load

Po = Xo.Fr + Yo.Fa

X_0	Y_0
0.6	0.5

For single or DT bearing arrangement :

If Po <Fr, then use Po = Fr