PDF technical sheet
61802EEG15



Single row deep groove ball bearings
Deep groove ball bearing, radial contact, polyamide cage, contact seals on both sides

Product definition	
d	0.5906 "
D	0.9449 "
B	0.1969 "
d1	0.7087 "
D1	0.8346 "
rs min	0.0118 "
Radial clearance class	CN
Mass	0.02 oz
Brand	SNR



Product performance	
Dynamic load, C	2.08 kN
Static load, C0	1.26 kN
Fatigue limit load, Cu	0.06 kN
f0	15.9
Nlim	16,000 RPM
Min operating temperature, Tmin	−4 °C
Max operating temperature, Tmax	248 °C
Characteristic cage frequency, FTF	0.44 Hz
Characteristic rolling element frequency, BSF	8.07 Hz
Characteristic outer ring frequency, BPF0	6.15 Hz
Characteristic inner ring frequency, BPFI	7.86 Hz



NTN-SNR ROULEMENTS – www.ntn-snr.com
1 rue des Usines – 74010 Annecy Cedex – France – Tel. +33 (0)4 50 65 30 00
S.A. au capital de 123 599 542 € - RCS ANNECY B 325 821 072 – Id. Fiscale : FR 48 325 821 072 – SIRET 325 821 072 00015 –
Code APE 2815 Z – Code NACE 28.15

Abutment dimensions	
da min	0.6693 "
da max	0.7087 "
Da max	0.8661 "
ra max	0.0118 "

Calculation factors

Equivalent dynamic radial load

P = X.Fr + Y.Fa

$\frac{f_0 F_a}{C_0}$	e	Fa / Fr ≤ e		Fa / Fr > e	
		X	Y	X	Y
0.172	0.19	1	0	0.56	2.3
0.345	0.22				1.99
0.689	0.26				1.71
1.03	0.28				1.55
1.38	0.3				1.45
2.07	0.34				1.31
3.45	0.38				1.15
5.17	0.42				1.04
6.89	0.44				1

Equivalent static radial load

Po = Xo.Fr + Yo.Fa

X_0	Y_0
0.6	0.5

For single or DT bearing arrangement :

If Po <Fr, then use Po = Fr