



PDF technical sheet 6200Z




Single row deep groove ball bearings

Deep groove ball bearing, radial contact, pressed steel cage, shield on one side

Product definition	
d	0.3937 "
D	1.1811 "
B	0.3543 "
d1	0.6299 "
D1	1.0118 "
rs min	0.0236 "
Radial clearance class	CN
Mass	0.12 oz
Brand	SNR



Product performance	
Dynamic load, C	5.90 kN
Static load, C0	2.60 kN
Fatigue limit load, Cu	0.12 kN
f0	12.1
Nref	23,000 RPM
Nlim	42,000 RPM
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	248 °C
Characteristic cage frequency, FTF	0.36 Hz
Characteristic rolling element frequency, BSF	3.32 Hz
Characteristic outer ring frequency, BPF0	2.53 Hz
Characteristic inner ring frequency, BPF1	4.47 Hz



Abutment dimensions

da min	0.5512 "
da max	0.6299 "
Da max	1.0236 "
ra max	0.0236 "

Calculation factors

Equivalent dynamic radial load

$$P = X.F_r + Y.F_a$$

$\frac{f_0 F_a}{C_0}$	e	$F_a / F_r \leq e$		$F_a / F_r > e$	
		X	Y	X	Y
0.172	0.19	1	0	0.56	2.3
0.345	0.22				1.99
0.689	0.26				1.71
1.03	0.28				1.55
1.38	0.3				1.45
2.07	0.34				1.31
3.45	0.38				1.15
5.17	0.42				1.04
6.89	0.44				1

Equivalent static radial load

$$P_0 = X_0.F_r + Y_0.F_a$$

X_0	Y_0
0.6	0.5

For single or DT bearing arrangement:

If $P_0 < F_r$, then use $P_0 = F_r$