

PDF technical sheet

23268BL1KC3

Double row spherical roller bearings

Spherical roller bearing, with central rib on inner ring, 2-part machined cage centred on inner ring, groove and lubrication holes on outer ring, tapered bore 1:12

Product definition	
d	13.3858 "
D	24.4094 "
B	8.8189 "
d2	17.0079 "
D1	20.6260 "
rs min	0.2362 "
Number of lubrication holes	8
b	1.2992 "
k	0.7874 "
Associated sleeve reference	H3268
e	0.37
Y1	1.84
Y2	2.75
Y0	1.8
Radial clearance class	C3
Brand	NTN

Product performance	
Dynamic load, C	4,450 kN
Static load, C0	8,000 kN
Fatigue limit load, Cu	502 kN
Nref	470 RPM
Nlim	850 RPM
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	248 °C
Characteristic cage frequency, FTF	0.43 Hz
Characteristic rolling element frequency, BSF	7.01 Hz
Characteristic outer ring frequency, BPF0	8.21 Hz
Characteristic inner ring frequency, BPFI	10.79 Hz

Abutment dimensions

da min	14.4094 "
db min	14.3307 "
Ce min	0.5512 "
Da max	23.3858 "
ra max	0.1969 "

Calculation factors

Equivalent dynamic radial load

$$P = X.F_r + Y.F_a$$

$F_a / F_r \leq e$		$F_a / F_r > e$	
X	Y	X	Y
1	Y1	0.67	Y2

Equivalent static radial load

$$P_0 = X_0.F_r + Y_0.F_a$$

X_0	Y_0
1	Y0

The values for e, Y1, Y2 and Y0 are shown in the above table .