

PDF technical sheet

23926EMD1



Double row spherical roller bearings

Spherical roller bearing, one-piece machined cage, groove and lubrication holes on outer ring

Product definition	
d	5.1181 "
D	7.0866 "
B	1.4567 "
d2	5.6693 "
D1	6.6142 "
rs min	0.0591 "
Number of lubrication holes	3
b	0.3110 "
k	0.1378 "
e	0.17
Y1	3.9
Y2	5.81
Y0	3.81
Radial clearance class	CN
Brand	NTN



Product performance	
Dynamic load, C	295 kN
Static load, C0	432 kN
Fatigue limit load, Cu	44.20 kN
Nref	2,500 RPM
Nlim	3,600 RPM
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	392 °C
Characteristic cage frequency, FTF	0.46 Hz
Characteristic rolling element frequency, BSF	13.05 Hz
Characteristic outer ring frequency, BPF0	15.25 Hz
Characteristic inner ring frequency, BPF1	17.75 Hz



Abutment dimensions

da min	5.3937 "
Da max	6.8110 "
ra max	0.0591 "

Calculation factors

Equivalent dynamic radial load

$$P = X.F_r + Y.F_a$$

Fa / Fr ≤ e		Fa / Fr > e	
X	Y	X	Y
1	Y1	0.67	Y2

Equivalent static radial load

$$P_0 = X_0.F_r + Y_0.F_a$$

X ₀	Y ₀
1	Y0

The values for e, Y1, Y2 and Y0 are shown in the above table .