

PDF technical sheet

23952EMD1



Double row spherical roller bearings

Spherical roller bearing, one-piece machined cage, groove and lubrication holes on outer ring

Product definition	
d	10.2362 "
D	14.1732 "
B	2.9528 "
d2	11.4961 "
D1	13.1890 "
rs min	0.0827 "
Number of lubrication holes	8
b	0.4331 "
k	0.2362 "
e	0.17
Y1	3.9
Y2	5.81
Y0	3.81
Radial clearance class	CN
Brand	NTN



Product performance	
Dynamic load, C	1,130 kN
Static load, C0	1,940 kN
Fatigue limit load, Cu	154 kN
Nref	1,200 RPM
Nlim	1,800 RPM
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	392 °C
Characteristic cage frequency, FTF	0.46 Hz
Characteristic rolling element frequency, BSF	13.84 Hz
Characteristic outer ring frequency, BPF0	17.18 Hz
Characteristic inner ring frequency, BPF1	19.82 Hz



Abutment dimensions

da min	10.6378 "
Da max	13.7717 "
ra max	0.0787 "

Calculation factors

Equivalent dynamic radial load

$$P = X.F_r + Y.F_a$$

$F_a / F_r \leq e$		$F_a / F_r > e$	
X	Y	X	Y
1	Y1	0.67	Y2

Equivalent static radial load

$$P_0 = X_0.F_r + Y_0.F_a$$

X_0	Y_0
1	Y0

The values for e, Y1, Y2 and Y0 are shown in the above table .