


PDF technical sheet 21308VKC3




Double row spherical roller bearings

Spherical roller bearing, pressed steel cage, tapered bore 1:12

Product definition	
d	1.5748 "
D	3.5433 "
B	0.9055 "
d2	2.1063 "
D1	2.9685 "
rs min	0.0591 "
Number of lubrication holes	
Associated sleeve reference	H308
e	0.26
Y1	2.55
Y2	3.8
Y0	2.5
Radial clearance class	C3
Mass	2.49 oz
Brand	SNR



Product performance	
Dynamic load, C	101 kN
Static load, C0	84.40 kN
Fatigue limit load, Cu	11.10 kN
Nref	6,400 RPM
Nlim	9,300 RPM
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	392 °C
Characteristic cage frequency, FTF	0.41 Hz
Characteristic rolling element frequency, BSF	5.56 Hz
Characteristic outer ring frequency, BPF0	5.80 Hz
Characteristic inner ring frequency, BPF1	8.20 Hz



Abutment dimensions

da min	1.9291 "
Da max	3.1890 "
ra max	0.0591 "

Calculation factors

Equivalent dynamic radial load

$$P = X.F_r + Y.F_a$$

Fa / Fr ≤ e		Fa / Fr > e	
X	Y	X	Y
1	Y1	0.67	Y2

Equivalent static radial load

$$P_0 = X_0.F_r + Y_0.F_a$$

X ₀	Y ₀
1	Y0

The values for e, Y1, Y2 and Y0 are shown in the above table .