


PDF technical sheet 21314VKC3




Double row spherical roller bearings

Spherical roller bearing, pressed steel cage, tapered bore 1:12

Product definition	
d	2.7559 "
D	5.9055 "
B	1.3780 "
d2	3.5945 "
D1	4.9921 "
rs min	0.0827 "
Number of lubrication holes	
Associated sleeve reference	H314
e	0.23
Y1	2.9
Y2	4.31
Y0	2.83
Radial clearance class	C3
Mass	10.41 oz
Brand	SNR



Product performance	
Dynamic load, C	259 kN
Static load, C0	240 kN
Fatigue limit load, Cu	30.90 kN
Nref	4,200 RPM
Nlim	5,500 RPM
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	392 °C
Characteristic cage frequency, FTF	0.42 Hz
Characteristic rolling element frequency, BSF	5.84 Hz
Characteristic outer ring frequency, BPF0	6.27 Hz
Characteristic inner ring frequency, BPF1	8.73 Hz



Abutment dimensions

da min	3.2283 "
Da max	5.4331 "
ra max	0.0787 "

Calculation factors

Equivalent dynamic radial load

$$P = X.F_r + Y.F_a$$

$F_a / F_r \leq e$		$F_a / F_r > e$	
X	Y	X	Y
1	Y1	0.67	Y2

Equivalent static radial load

$$P_0 = X_0.F_r + Y_0.F_a$$

X_0	Y_0
1	Y0

The values for e, Y1, Y2 and Y0 are shown in the above table .