

PDF technical sheet


22210EAC4




Double row spherical roller bearings

Spherical roller bearing, pressed steel cage

Product definition	
d	1.9685 "
D	3.5433 "
B	0.9055 "
d2	2.3425 "
D1	3.1772 "
rs min	0.0433 "
Number of lubrication holes	
e	0.24
Y1	2.84
Y2	4.23
Y0	2.78
Radial clearance class	C4
Mass	2.13 oz
Brand	SNR



Product performance	
Dynamic load, C	130 kN
Static load, C0	124 kN
Fatigue limit load, Cu	14.50 kN
Nref	6,700 RPM
Nlim	9,100 RPM
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	392 °C
Characteristic cage frequency, FTF	0.42 Hz
Characteristic rolling element frequency, BSF	6.34 Hz
Characteristic outer ring frequency, BPF0	7.63 Hz
Characteristic inner ring frequency, BPF1	10.37 Hz



Abutment dimensions

da min	2.2441 "
Da max	3.2677 "
ra max	0.0394 "

Calculation factors

Equivalent dynamic radial load

$$P = X.F_r + Y.F_a$$

Fa / Fr ≤ e		Fa / Fr > e	
X	Y	X	Y
1	Y1	0.67	Y2

Equivalent static radial load

$$P_0 = X_0.F_r + Y_0.F_a$$

X ₀	Y ₀
1	Y0

The values for e, Y1, Y2 and Y0 are shown in the above table .