


PDF technical sheet 22213EG15KW33C4



Double row spherical roller bearings

Spherical roller bearing, polyamide cage, groove and lubrication holes on outer ring, tapered bore 1:12

Product definition	
d	2.5591 "
D	4.7244 "
B	1.2205 "
d2	3.0787 "
D1	4.2126 "
rs min	0.0591 "
Number of lubrication holes	3
b	0.3071 "
k	0.1378 "
Associated sleeve reference	H313
e	0.24
Y1	2.79
Y2	4.15
Y0	2.73
Radial clearance class	C4
Mass	5.17 oz
Brand	SNR



Product performance	
Dynamic load, C	226 kN
Static load, C0	224 kN
Fatigue limit load, Cu	26 kN
Nref	5,300 RPM
Nlim	6,900 RPM
Min operating temperature, Tmin	-4 °C
Max operating temperature, Tmax	248 °C
Characteristic cage frequency, FTF	0.42 Hz
Characteristic rolling element frequency, BSF	6.18 Hz
Characteristic outer ring frequency, BPF0	7.60 Hz
Characteristic inner ring frequency, BPF1	10.40 Hz



Abutment dimensions

da min	2.9134 "
Da max	4.3701 "
ra max	0.0591 "

Calculation factors

Equivalent dynamic radial load

$$P = X.F_r + Y.F_a$$

Fa / Fr ≤ e		Fa / Fr > e	
X	Y	X	Y
1	Y1	0.67	Y2

Equivalent static radial load

$$P_0 = X_0.F_r + Y_0.F_a$$

X ₀	Y ₀
1	Y0

The values for e, Y1, Y2 and Y0 are shown in the above table .