

PDF technical sheet

22216EMW33C3



Double row spherical roller bearings

Spherical roller bearing, one-piece machined cage, groove and lubrication holes on outer ring

Product definition	
d	3.1496 "
D	5.5118 "
B	1.2992 "
D1	4.9882 "
rs min	0.0787 "
Number of lubrication holes	3
b	0.3110 "
k	0.1378 "
e	0.22
Y1	3.13
Y2	4.67
Y0	3.06
Radial clearance class	C3
Mass	7.61 oz
Brand	SNR



Product performance	
Dynamic load, C	267 kN
Static load, C0	272 kN
Fatigue limit load, Cu	32.50 kN
Nref	4,300 RPM
Nlim	5,800 RPM
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	392 °C
Characteristic cage frequency, FTF	0.43 Hz
Characteristic rolling element frequency, BSF	6.68 Hz
Characteristic outer ring frequency, BPF0	7.70 Hz
Characteristic inner ring frequency, BPF1	10.31 Hz



Abutment dimensions

da min	3.5827 "
Da max	5.0787 "
ra max	0.0787 "

Calculation factors

Equivalent dynamic radial load

$$P = X.F_r + Y.F_a$$

Fa / Fr ≤ e		Fa / Fr > e	
X	Y	X	Y
1	Y1	0.67	Y2

Equivalent static radial load

$$P_0 = X_0.F_r + Y_0.F_a$$

X ₀	Y ₀
1	Y0

The values for e, Y1, Y2 and Y0 are shown in the above table .