

PDF technical sheet


22218EG15W33C3




Double row spherical roller bearings

Spherical roller bearing, polyamide cage, groove and lubrication holes on outer ring

Product definition	
d	3.5433 "
D	6.2992 "
B	1.5748 "
d2	4.1457 "
D1	5.6378 "
rs min	0.0787 "
Number of lubrication holes	3
b	0.4016 "
k	0.1772 "
e	0.23
Y1	2.9
Y2	4.31
Y0	2.83
Radial clearance class	C3
Mass	11.58 oz
Brand	SNR



Product performance	
Dynamic load, C	384 kN
Static load, C0	398 kN
Fatigue limit load, Cu	43.10 kN
Nref	3,900 RPM
Nlim	5,100 RPM
Min operating temperature, Tmin	-4 °C
Max operating temperature, Tmax	248 °C
Characteristic cage frequency, FTF	0.42 Hz
Characteristic rolling element frequency, BSF	6.24 Hz
Characteristic outer ring frequency, BPF0	7.61 Hz
Characteristic inner ring frequency, BPF1	10.39 Hz



Abutment dimensions

da min	3.9764 "
Da max	5.8661 "
ra max	0.0787 "

Calculation factors

Equivalent dynamic radial load

$$P = X.F_r + Y.F_a$$

Fa / Fr ≤ e		Fa / Fr > e	
X	Y	X	Y
1	Y1	0.67	Y2

Equivalent static radial load

$$P_0 = X_0.F_r + Y_0.F_a$$

X ₀	Y ₀
1	Y0

The values for e, Y1, Y2 and Y0 are shown in the above table .