


PDF technical sheet 22322EF803




Double row spherical roller bearings

Spherical roller bearing for vibratory applications, one-piece machined cage, groove and lubrication holes on outer ring, special C5 class clearance

Product definition	
d	4.3307 "
D	9.4488 "
B	3.1496 "
d2	5.4685 "
D1	8.1929 "
rs min	0.1181 "
Number of lubrication holes	3
b	0.6142 "
k	0.2756 "
e	0.32
Y1	2.09
Y2	3.11
Y0	2.04
Radial clearance class	C5 Special
Mass	61.40 oz
Brand	SNR



Product performance	
Dynamic load, C	975 kN
Static load, C0	972 kN
Fatigue limit load, Cu	84.50 kN
Nref	2,300 RPM
Nlim	2,800 RPM
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	392 °C
Characteristic cage frequency, FTF	0.40 Hz
Characteristic rolling element frequency, BSF	4.70 Hz
Characteristic outer ring frequency, BPF0	5.60 Hz
Characteristic inner ring frequency, BPF1	8.40 Hz



Abutment dimensions

da min	4.8819 "
Da max	8.8976 "
ra max	0.0984 "

Calculation factors

Equivalent dynamic radial load

$$P = X.F_r + Y.F_a$$

Fa / Fr ≤ e		Fa / Fr > e	
X	Y	X	Y
1	Y1	0.67	Y2

Equivalent static radial load

$$P_0 = X_0.F_r + Y_0.F_a$$

X ₀	Y ₀
1	Y0

The values for e, Y1, Y2 and Y0 are shown in the above table .