

PDF technical sheet 23022EAKW33



Double row spherical roller bearings

Spherical roller bearing, pressed steel cage, groove and lubrication holes on outer ring, tapered bore 1:12

Product definition	
d	4.3307 "
D	6.6929 "
B	1.7717 "
d2	4.8740 "
D1	6.0866 "
rs min	0.0787 "
Number of lubrication holes	3
b	0.3071 "
k	0.1378 "
Associated sleeve reference	H322
e	0.23
Y1	2.95
Y2	4.4
Y0	2.89
Radial clearance class	CN
Mass	12.17 oz
Brand	SNR



Product performance	
Dynamic load, C	417 kN
Static load, C0	517 kN
Fatigue limit load, Cu	46.20 kN
Nref	3,500 RPM
Nlim	4,200 RPM
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	392 °C
Characteristic cage frequency, FTF	0.44 Hz
Characteristic rolling element frequency, BSF	8.45 Hz
Characteristic outer ring frequency, BPF0	10.17 Hz
Characteristic inner ring frequency, BPF1	12.83 Hz



Abutment dimensions

da min	4.6772 "
Da max	6.3465 "
ra max	0.0787 "

Calculation factors

Equivalent dynamic radial load

$$P = X.F_r + Y.F_a$$

Fa / Fr ≤ e		Fa / Fr > e	
X	Y	X	Y
1	Y1	0.67	Y2

Equivalent static radial load

$$P_0 = X_0.F_r + Y_0.F_a$$

X ₀	Y ₀
1	Y0

The values for e, Y1, Y2 and Y0 are shown in the above table .