

PDF technical sheet

23048EMW33



Double row spherical roller bearings

Spherical roller bearing, one-piece machined cage, groove and lubrication holes on outer ring

Product definition	
d	9.4488 "
D	14.1732 "
B	3.6220 "
D1	12.9488 "
rs min	0.1181 "
Number of lubrication holes	3
b	0.6457 "
k	0.3150 "
e	0.22
Y1	3.07
Y2	4.58
Y0	3.01
Radial clearance class	CN
Mass	115.35 oz
Brand	SNR



Product performance	
Dynamic load, C	1,630 kN
Static load, C0	2,350 kN
Fatigue limit load, Cu	173 kN
Nref	1,400 RPM
Nlim	2,000 RPM
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	392 °C
Characteristic cage frequency, FTF	0.45 Hz
Characteristic rolling element frequency, BSF	9.13 Hz
Characteristic outer ring frequency, BPF0	11.61 Hz
Characteristic inner ring frequency, BPF1	14.39 Hz



Abutment dimensions

da min	9.9370 "
Da max	13.6850 "
ra max	0.0984 "

Calculation factors

Equivalent dynamic radial load

$$P = X.F_r + Y.F_a$$

$F_a / F_r \leq e$		$F_a / F_r > e$	
X	Y	X	Y
1	Y1	0.67	Y2

Equivalent static radial load

$$P_0 = X_0.F_r + Y_0.F_a$$

X_0	Y_0
1	Y0

The values for e, Y1, Y2 and Y0 are shown in the above table .