

PDF technical sheet 23148EMW33C4



Double row spherical roller bearings

Spherical roller bearing, one-piece machined cage, groove and lubrication holes on outer ring

Product definition	
d	9.4488 "
D	15.7480 "
B	5.0394 "
D1	13.9882 "
rs min	0.1575 "
Number of lubrication holes	3
b	0.7717 "
k	0.3543 "
e	0.29
Y1	2.32
Y2	3.45
Y0	2.26
Radial clearance class	C4
Mass	228.29 oz
Brand	SNR



Product performance	
Dynamic load, C	2,510 kN
Static load, C0	3,500 kN
Fatigue limit load, Cu	212 kN
Nref	1,100 RPM
Nlim	1,600 RPM
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	392 °C
Characteristic cage frequency, FTF	0.44 Hz
Characteristic rolling element frequency, BSF	7.46 Hz
Characteristic outer ring frequency, BPF0	9.58 Hz
Characteristic inner ring frequency, BPF1	12.42 Hz



Abutment dimensions

da min	10.1181 "
Da max	15.0787 "
ra max	0.1181 "

Calculation factors

Equivalent dynamic radial load

$$P = X.F_r + Y.F_a$$

Fa / Fr ≤ e		Fa / Fr > e	
X	Y	X	Y
1	Y1	0.67	Y2

Equivalent static radial load

$$P_0 = X_0.F_r + Y_0.F_a$$

X ₀	Y ₀
1	Y0

The values for e, Y1, Y2 and Y0 are shown in the above table .