

PDF technical sheet 23226EMKW33C4



Double row spherical roller bearings

Spherical roller bearing, one-piece machined cage, groove and lubrication holes on outer ring, tapered bore 1:12

Product definition	
d	5.1181 "
D	9.0551 "
B	3.1496 "
d2	5.9331 "
D1	7.9803 "
rs min	0.1181 "
Number of lubrication holes	3
b	0.4567 "
k	0.1969 "
Associated sleeve reference	H2326
e	0.32
Y1	2.12
Y2	3.15
Y0	2.07
Radial clearance class	C4
Mass	47.20 oz
Brand	SNR



Product performance	
Dynamic load, C	958 kN
Static load, C0	1,130 kN
Fatigue limit load, Cu	80.20 kN
Nref	1,900 RPM
Nlim	2,600 RPM
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	392 °C
Characteristic cage frequency, FTF	0.42 Hz
Characteristic rolling element frequency, BSF	6.33 Hz
Characteristic outer ring frequency, BPF0	7.64 Hz
Characteristic inner ring frequency, BPF1	10.36 Hz



Abutment dimensions

da min	5.6693 "
db min	5.5906 "
Ce min	0.8268 "
Da max	8.5039 "
ra max	0.0984 "

Calculation factors

Equivalent dynamic radial load

$$P = X.F_r + Y.F_a$$

$F_a / F_r \leq e$		$F_a / F_r > e$	
X	Y	X	Y
1	Y1	0.67	Y2

Equivalent static radial load

$$P_0 = X_0.F_r + Y_0.F_a$$

X_0	Y_0
1	Y0

The values for e, Y1, Y2 and Y0 are shown in the above table .