


PDF technical sheet 23238EMKW33C4




Double row spherical roller bearings

Spherical roller bearing, one-piece machined cage, groove and lubrication holes on outer ring, tapered bore 1:12

Product definition	
d	7.4803 "
D	13.3858 "
B	4.7244 "
d2	8.6929 "
D1	11.7362 "
rs min	0.1575 "
Number of lubrication holes	3
b	0.6890 "
k	0.3150 "
Associated sleeve reference	H2338
e	0.33
Y1	2.03
Y2	3.02
Y0	1.98
Radial clearance class	C4
Mass	157.32 oz
Brand	SNR



Product performance	
Dynamic load, C	1,990 kN
Static load, C0	2,480 kN
Fatigue limit load, Cu	153 kN
Nref	1,200 RPM
Nlim	1,800 RPM
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	392 °C
Characteristic cage frequency, FTF	0.42 Hz
Characteristic rolling element frequency, BSF	6.25 Hz
Characteristic outer ring frequency, BPF0	7.63 Hz
Characteristic inner ring frequency, BPF1	10.37 Hz



Abutment dimensions

da min	8.1496 "
db min	8.1102 "
Ce min	0.8268 "
Da max	12.7165 "
ra max	0.1181 "

Calculation factors

Equivalent dynamic radial load

$$P = X.F_r + Y.F_a$$

$F_a / F_r \leq e$		$F_a / F_r > e$	
X	Y	X	Y
1	Y1	0.67	Y2

Equivalent static radial load

$$P_0 = X_0.F_r + Y_0.F_a$$

X_0	Y_0
1	Y0

The values for e, Y1, Y2 and Y0 are shown in the above table .