

PDF technical sheet 23240EMKW33C3



Double row spherical roller bearings

Spherical roller bearing, one-piece machined cage, groove and lubrication holes on outer ring, tapered bore 1:12

Product definition	
d	7.8740 "
D	14.1732 "
B	5.0394 "
D1	12.3937 "
rs min	0.1575 "
Number of lubrication holes	3
b	0.7402 "
k	0.3543 "
Associated sleeve reference	H2340
e	0.34
Y1	1.98
Y2	2.94
Y0	1.93
Radial clearance class	C3
Mass	196.83 oz
Brand	SNR



Product performance	
Dynamic load, C	2,250 kN
Static load, C0	2,840 kN
Fatigue limit load, Cu	173 kN
Nref	1,100 RPM
Nlim	1,700 RPM
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	392 °C
Characteristic cage frequency, FTF	0.42 Hz
Characteristic rolling element frequency, BSF	6.21 Hz
Characteristic outer ring frequency, BPF0	7.62 Hz
Characteristic inner ring frequency, BPF1	10.38 Hz



Abutment dimensions

da min	8.5433 "
Da max	13.5039 "
ra max	0.1181 "

Calculation factors

Equivalent dynamic radial load

$$P = X.F_r + Y.F_a$$

Fa / Fr ≤ e		Fa / Fr > e	
X	Y	X	Y
1	Y1	0.67	Y2

Equivalent static radial load

$$P_0 = X_0.F_r + Y_0.F_a$$

X ₀	Y ₀
1	Y0

The values for e, Y1, Y2 and Y0 are shown in the above table .