


PDF technical sheet 23244EMKW33C3




Double row spherical roller bearings

Spherical roller bearing, one-piece machined cage, groove and lubrication holes on outer ring, tapered bore 1:12

Product definition	
d	8.6614 "
D	15.7480 "
B	5.6693 "
D1	13.7205 "
rs min	0.1575 "
Number of lubrication holes	3
b	0.7874 "
k	0.3937 "
Associated sleeve reference	H2344H
e	0.34
Y1	2
Y2	2.98
Y0	1.96
Radial clearance class	C3
Mass	263.85 oz
Brand	SNR



Product performance	
Dynamic load, C	2,890 kN
Static load, C0	3,830 kN
Fatigue limit load, Cu	211 kN
Nref	850 RPM
Nlim	1,500 RPM
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	392 °C
Characteristic cage frequency, FTF	0.43 Hz
Characteristic rolling element frequency, BSF	6.41 Hz
Characteristic outer ring frequency, BPF0	8.09 Hz
Characteristic inner ring frequency, BPF1	10.92 Hz



Abutment dimensions

da min	9.3307 "
Da max	15.0787 "
ra max	0.1181 "

Calculation factors

Equivalent dynamic radial load

$$P = X.F_r + Y.F_a$$

$F_a / F_r \leq e$		$F_a / F_r > e$	
X	Y	X	Y
1	Y1	0.67	Y2

Equivalent static radial load

$$P_0 = X_0.F_r + Y_0.F_a$$

X_0	Y_0
1	Y0

The values for e, Y1, Y2 and Y0 are shown in the above table .