


PDF technical sheet 23248EMKW33C3




Double row spherical roller bearings

Spherical roller bearing, one-piece machined cage, groove and lubrication holes on outer ring, tapered bore 1:12

Product definition	
d	9.4488 "
D	17.3228 "
B	6.2992 "
D1	15.0433 "
rs min	0.1575 "
Number of lubrication holes	8
b	1.0630 "
k	0.6299 "
Associated sleeve reference	H2348H
e	0.35
Y1	1.95
Y2	2.9
Y0	1.91
Radial clearance class	C3
Mass	378.95 oz
Brand	SNR



Product performance	
Dynamic load, C	3,270 kN
Static load, C0	4,440 kN
Fatigue limit load, Cu	237 kN
Nref	800 RPM
Nlim	1,400 RPM
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	392 °C
Characteristic cage frequency, FTF	0.43 Hz
Characteristic rolling element frequency, BSF	6.69 Hz
Characteristic outer ring frequency, BPF0	8.14 Hz
Characteristic inner ring frequency, BPF1	10.86 Hz



Abutment dimensions

da min	10.1181 "
Da max	16.6535 "
ra max	0.1181 "

Calculation factors

Equivalent dynamic radial load

$$P = X.F_r + Y.F_a$$

Fa / Fr ≤ e		Fa / Fr > e	
X	Y	X	Y
1	Y1	0.67	Y2

Equivalent static radial load

$$P_0 = X_0.F_r + Y_0.F_a$$

X ₀	Y ₀
1	Y0

The values for e, Y1, Y2 and Y0 are shown in the above table .