

PDF technical sheet 23260EMKW33C3



Double row spherical roller bearings

Spherical roller bearing, one-piece machined cage, groove and lubrication holes on outer ring, tapered bore 1:12

Product definition	
d	11.8110 "
D	21.2598 "
B	7.5591 "
D1	18.4016 "
rs min	0.1969 "
Number of lubrication holes	8
b	1.0630 "
k	0.6299 "
Associated sleeve reference	H3260H
e	0.34
Y1	1.98
Y2	2.94
Y0	1.93
Radial clearance class	C3
Mass	722.06 oz
Brand	SNR



Product performance	
Dynamic load, C	4,880 kN
Static load, C0	6,880 kN
Fatigue limit load, Cu	352 kN
Nref	560 RPM
Nlim	1,100 RPM
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	392 °C
Characteristic cage frequency, FTF	0.43 Hz
Characteristic rolling element frequency, BSF	6.65 Hz
Characteristic outer ring frequency, BPF0	8.57 Hz
Characteristic inner ring frequency, BPF1	11.44 Hz



Abutment dimensions

da min	12.5984 "
Da max	20.4724 "
ra max	0.1575 "

Calculation factors

Equivalent dynamic radial load

$$P = X.F_r + Y.F_a$$

$F_a / F_r \leq e$		$F_a / F_r > e$	
X	Y	X	Y
1	Y1	0.67	Y2

Equivalent static radial load

$$P_0 = X_0.F_r + Y_0.F_a$$

X_0	Y_0
1	Y0

The values for e, Y1, Y2 and Y0 are shown in the above table .