

PDF technical sheet

24026EAK30W33

Double row spherical roller bearings

Spherical roller bearing, pressed steel cage, groove and lubrication holes on outer ring, tapered bore 1:30, non ISO width, contact seals on both sides

Product definition	
d	5.1181 "
D	7.8740 "
B	2.7165 "
d2	5.6299 "
D1	7.0315 "
rs min	0.0787 "
Number of lubrication holes	3
b	0.3283 "
k	0.1575 "
e	0.31
Y1	2.18
Y2	3.25
Y0	2.13
Radial clearance class	CN
Mass	26.46 oz
Brand	SNR

Product performance	
Dynamic load, C	684 kN
Static load, C0	909 kN
Fatigue limit load, Cu	62.50 kN
Nref	2,300 RPM
Nlim	3,100 RPM
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	392 °C
Characteristic cage frequency, FTF	0.44 Hz
Characteristic rolling element frequency, BSF	8.26 Hz
Characteristic outer ring frequency, BPF0	10.16 Hz
Characteristic inner ring frequency, BPF1	12.85 Hz

Abutment dimensions	
da min	5.4646 "
Da max	7.5276 "
ra max	0.0787 "

Calculation factors

Equivalent dynamic radial load

$$P = X.F_r + Y.F_a$$

$F_a / F_r \leq e$		$F_a / F_r > e$	
X	Y	X	Y
1	Y1	0.67	Y2

Equivalent static radial load

$$P_0 = X_0.F_r + Y_0.F_a$$

X_0	Y_0
1	Y0

The values for e, Y1, Y2 and Y0 are shown in the above table .