


PDF technical sheet 24144EMW33




Double row spherical roller bearings

Spherical roller bearing, with central rib on inner ring, one-piece machined cage centred on inner ring, groove and lubrication holes on outer ring

Product definition	
d	8.6614 "
D	14.5669 "
B	5.9055 "
D1	12.6102 "
rs min	0.1575 "
Number of lubrication holes	3
b	0.6260 "
k	0.2756 "
e	0.39
Y1	1.74
Y2	2.59
Y0	1.7
Radial clearance class	CN
Mass	223.99 oz
Brand	SNR



Product performance	
Dynamic load, C	2,600 kN
Static load, C0	3,540 kN
Fatigue limit load, Cu	178 kN
Nref	850 RPM
Nlim	1,400 RPM
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	392 °C
Characteristic cage frequency, FTF	0.43 Hz
Characteristic rolling element frequency, BSF	6.74 Hz
Characteristic outer ring frequency, BPF0	8.16 Hz
Characteristic inner ring frequency, BPF1	10.84 Hz



Abutment dimensions

da min	9.3307 "
Da max	13.8976 "
ra max	0.1181 "

Calculation factors

Equivalent dynamic radial load

$$P = X.F_r + Y.F_a$$

Fa / Fr ≤ e		Fa / Fr > e	
X	Y	X	Y
1	Y1	0.67	Y2

Equivalent static radial load

$$P_0 = X_0.F_r + Y_0.F_a$$

X ₀	Y ₀
1	Y0

The values for e, Y1, Y2 and Y0 are shown in the above table .