

PDF technical sheet 30330



Single row tapered roller bearings

Tapered roller bearing, pressed steel cage

Product definition	
d	5.9055 "
D	12.5984 "
B	2.5591 "
C	2.1654 "
T	2.8346 "
d1	8.9173 "
a	2.4606 "
rs min	0.1575 "
r1s min	0.1575 "
e	0.37
Y2	1.6
Y0	0.88
Mass	87.13 oz
Brand	NTN



Product performance	
Dynamic load, C	680 kN
Rating life coefficient, A2	1
Static load, C0	875 kN
Fatigue limit load, Cu	82.50 kN
Nlim (oil)	1,600 RPM
Nlim (grease)	1,200 RPM
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	248 °C
Characteristic cage frequency, FTF	0.42 Hz
Characteristic rolling element frequency, BSF	5.80 Hz
Characteristic outer ring frequency, BPF0	6.28 Hz
Characteristic inner ring frequency, BPFI	8.72 Hz



Abutment dimensions

da max	7.5984 "
db min	6.7717 "
Da min	10.5906 "
Da max	11.8898 "
Db min	11.4961 "
Ca min	0.3150 "
Cb min	0.6693 "
ra max	0.1575 "
r1a max	0.1181 "

Calculation factors

Equivalent dynamic radial load

$$P = X.F_r + Y.F_a$$

$F_a / F_r \leq e$		$F_a / F_r > e$	
X	Y	X	Y
1	0	0.4	Y2

Equivalent static radial load

$$P_0 = X_0.F_r + Y_0.F_a$$

X_0	Y_0
0.5	Y0

If $P_0 \leq F_r$, then use $P_0 = F_r$

The values for e, Y2 and Y0 are shown in the above table