

PDF technical sheet 30332U



Single row tapered roller bearings

Tapered roller bearing, pressed steel cage

Product definition	
d	6.2992 "
D	13.3858 "
B	2.6772 "
C	2.2835 "
T	2.9528 "
d1	9.4094 "
a	2.5197 "
rs min	0.1969 "
r1s min	0.1575 "
e	0.35
Y2	1.74
Y0	0.96
Mass	105.47 oz
ISO 355 reference	T2GB160
Brand	NTN



Product performance	
Dynamic load, C	915 kN
Rating life coefficient, A2	1
Static load, C0	1,200 kN
Fatigue limit load, Cu	111 kN
Nlim (oil)	1,500 RPM
Nlim (grease)	1,100 RPM
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	248 °C
Characteristic cage frequency, FTF	0.41 Hz
Characteristic rolling element frequency, BSF	5.38 Hz
Characteristic outer ring frequency, BPF0	6.60 Hz
Characteristic inner ring frequency, BPFI	9.40 Hz



Abutment dimensions

da max	8.0709 "
db min	7.1654 "
Da min	11.2598 "
Da max	12.6772 "
Db min	12.2047 "
Ca min	0.3937 "
Cb min	0.6693 "
ra max	0.1575 "
r1a max	0.1181 "

Calculation factors

Equivalent dynamic radial load

$$P = X.F_r + Y.F_a$$

$F_a / F_r \leq e$		$F_a / F_r > e$	
X	Y	X	Y
1	0	0.4	Y2

Equivalent static radial load

$$P_0 = X_0.F_r + Y_0.F_a$$

X_0	Y_0
0.5	Y0

If $P_0 \leq F_r$, then use $P_0 = F_r$

The values for e, Y2 and Y0 are shown in the above table