

PDF technical sheet

32028XUP5




Single row tapered roller bearings

Tapered roller bearing, pressed steel cage

Product definition	
d	5.5118 "
D	8.2677 "
B	1.7717 "
C	1.3386 "
T	1.7717 "
d1	6.9291 "
a	1.8110 "
rs min	0.0984 "
r1s min	0.0787 "
e	0.46
Y2	1.31
Y0	0.72
Mass	18.62 oz
ISO 355 reference	T4DC140
Brand	NTN



Product performance	
Dynamic load, C	330 kN
Rating life coefficient, A2	1
Static load, C0	580 kN
Fatigue limit load, Cu	59.80 kN
Nlim (oil)	2,100 RPM
Nlim (grease)	1,600 RPM
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	248 °C
Characteristic cage frequency, FTF	0.46 Hz
Characteristic rolling element frequency, BSF	10.47 Hz
Characteristic outer ring frequency, BPF0	13.64 Hz
Characteristic inner ring frequency, BPFI	16.36 Hz



Abutment dimensions

da max	6.0236 "
db min	5.9843 "
Da min	7.3622 "
Da max	7.8740 "
Db min	7.9528 "
Ca min	0.3150 "
Cb min	0.4331 "
ra max	0.0787 "
r1a max	0.0787 "

Calculation factors

Equivalent dynamic radial load

$$P = X.F_r + Y.F_a$$

Fa / Fr ≤ e		Fa / Fr > e	
X	Y	X	Y
1	0	0.4	Y2

Equivalent static radial load

$$P_o = X_o.F_r + Y_o.F_a$$

X ₀	Y ₀
0.5	Y0

If $P_o \leq F_r$, then use $P_o = F_r$

The values for e, Y2 and Y0 are shown in the above table