PDF technical sheet
32221U

Single row tapered roller bearings
Tapered roller bearing, pressed steel cage

Product definition	
d	4.1339 "
D	7.4803 "
B	1.9685 "
C	1.6929 "
T	2.0866 "
a	1.7323 "
rs min	0.0984 "
r1s min	0.0787 "
e	0.42
Y2	1.43
Y0	0.79
Mass	22.05 oz
ISO 355 reference	T3FC105
Brand	NTN



Product performance	
Dynamic load, C	380 kN
Rating life coefficient, A2	1
Static load, C0	540 kN
Nlim (oil)	2,500 RPM
Nlim (grease)	1,900 RPM
Min operating temperature, Tmin	−40 °C
Max operating temperature, Tmax	248 °C



NTN-SNR ROULEMENTS – www.ntn-snr.com
1 rue des Usines – 74010 Annecy Cedex – France – Tel. +33 (0)4 50 65 30 00
S.A. au capital de 123 599 542 € - RCS ANNECY B 325 821 072 – Id. Fiscale : FR 48 325 821 072 – SIRET 325 821 072 00015 –
Code APE 2815 Z – Code NACE 28.15

Abutment dimensions	
da max	4.6850 "
db min	4.6850 "
Da max	7.0079 "
Db min	7.0866 "
ra max	0.0984 "
r1a max	0.0787 "

Calculation factors

Equivalent dynamic radial load

P = X.Fr + Y.Fa

Fa / Fr ≤ e		Fa / Fr > e	
X	Y	X	Y
1	0	0.4	Y2

Equivalent static radial load

Po= Xo.Fr + Yo.Fa

X_0	Y_0
0.5	Y0

If Po <Fr, then use Po = Fr

The values for e, Y2 and Y0 are shown in the above table