

PDF technical sheet 32226U



Single row tapered roller bearings

Tapered roller bearing, pressed steel cage

Product definition	
d	5.1181 "
D	9.0551 "
B	2.5197 "
C	2.1260 "
T	2.6673 "
d1	7.0866 "
a	2.2441 "
rs min	0.1575 "
r1s min	0.1181 "
e	0.44
Y2	1.38
Y0	0.76
Mass	39.51 oz
ISO 355 reference	T4FD130
Brand	NTN



Product performance	
Dynamic load, C	530 kN
Rating life coefficient, A2	1
Static load, C0	815 kN
Fatigue limit load, Cu	83.40 kN
Nlim (oil)	2,000 RPM
Nlim (grease)	1,500 RPM
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	248 °C
Characteristic cage frequency, FTF	0.44 Hz
Characteristic rolling element frequency, BSF	7.25 Hz
Characteristic outer ring frequency, BPF0	8.70 Hz
Characteristic inner ring frequency, BPFI	11.30 Hz



Abutment dimensions

da max	5.7480 "
db min	5.8268 "
Da min	7.5984 "
Da max	8.5039 "
Db min	8.6220 "
Ca min	0.2756 "
Cb min	0.5315 "
ra max	0.1181 "
r1a max	0.0984 "

Calculation factors

Equivalent dynamic radial load

$$P = X.F_r + Y.F_a$$

$F_a / F_r \leq e$		$F_a / F_r > e$	
X	Y	X	Y
1	0	0.4	Y2

Equivalent static radial load

$$P_0 = X_0.F_r + Y_0.F_a$$

X_0	Y_0
0.5	Y0

If $P_0 \leq F_r$, then use $P_0 = F_r$

The values for e, Y2 and Y0 are shown in the above table