

PDF technical sheet

32314U



Single row tapered roller bearings

Tapered roller bearing, pressed steel cage

Product definition	
d	2.7559 "
D	5.9055 "
B	2.0079 "
C	1.6535 "
T	2.1260 "
d1	4.2323 "
a	1.4370 "
rs min	0.1181 "
r1s min	0.0984 "
e	0.35
Y2	1.74
Y0	0.96
Mass	15.73 oz
ISO 355 reference	T2GD070
Brand	NTN



Product performance	
Dynamic load, C	310 kN
Rating life coefficient, A2	1
Static load, C0	405 kN
Fatigue limit load, Cu	48 kN
Nlim (oil)	3,500 RPM
Nlim (grease)	2,600 RPM
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	248 °C
Characteristic cage frequency, FTF	0.41 Hz
Characteristic rolling element frequency, BSF	5.27 Hz
Characteristic outer ring frequency, BPF0	6.57 Hz
Characteristic inner ring frequency, BPFI	9.43 Hz



Abutment dimensions

da max	3.3858 "
db min	3.3071 "
Da min	4.9213 "
Da max	5.4331 "
Db min	5.5118 "
Ca min	0.1575 "
Cb min	0.4724 "
ra max	0.0984 "
r1a max	0.0787 "

Calculation factors

Equivalent dynamic radial load

$$P = X.F_r + Y.F_a$$

$F_a / F_r \leq e$		$F_a / F_r > e$	
X	Y	X	Y
1	0	0.4	Y2

Equivalent static radial load

$$P_o = X_o.F_r + Y_o.F_a$$

X_o	Y_o
0.5	Y0

If $P_o \leq F_r$, then use $P_o = F_r$

The values for e, Y2 and Y0 are shown in the above table