

PDF technical sheet

32322U




Single row tapered roller bearings

Tapered roller bearing, pressed steel cage

Product definition	
d	4.3307 "
D	9.4488 "
B	3.1496 "
C	2.5591 "
T	3.3268 "
a	2.2638 "
rs min	0.1181 "
r1s min	0.0984 "
e	0.35
Y2	1.74
Y0	0.96
Mass	63.49 oz
ISO 355 reference	T2GD110
Brand	NTN



Product performance	
Dynamic load, C	705 kN
Rating life coefficient, A2	1
Static load, C0	970 kN
Nlim (oil)	2,200 RPM
Nlim (grease)	1,600 RPM
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	248 °C



Abutment dimensions

da max	5.0394 "
db min	5.3150 "
Da max	8.8976 "
Db min	8.7402 "
ra max	0.1181 "
r1a max	0.0984 "

Calculation factors

Equivalent dynamic radial load

$$P = X.F_r + Y.F_a$$

$F_a / F_r \leq e$		$F_a / F_r > e$	
X	Y	X	Y
1	0	0.4	Y2

Equivalent static radial load

$$P_0 = X_0.F_r + Y_0.F_a$$

X_0	Y_0
0.5	Y0

If $P_0 < F_r$, then use $P_0 = F_r$

The values for e, Y2 and Y0 are shown in the above table