

PDF technical sheet

32932XU



Single row tapered roller bearings

Tapered roller bearing, pressed steel cage

Product definition	
d	6.2992 "
D	8.6614 "
B	1.4961 "
C	1.1811 "
T	1.4961 "
d1	7.4803 "
a	1.5157 "
rs min	0.0984 "
r1s min	0.0787 "
e	0.35
Y2	1.73
Y0	0.95
Mass	14.64 oz
ISO 355 reference	T2DC160
Brand	NTN



Product performance	
Dynamic load, C	276 kN
Rating life coefficient, A2	1
Static load, C0	520 kN
Fatigue limit load, Cu	52.30 kN
Nlim (oil)	1,900 RPM
Nlim (grease)	1,500 RPM
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	248 °C
Characteristic cage frequency, FTF	0.46 Hz
Characteristic rolling element frequency, BSF	13.03 Hz
Characteristic outer ring frequency, BPF0	15.74 Hz
Characteristic inner ring frequency, BPFI	18.27 Hz



Abutment dimensions

da max	6.7126 "
db min	6.7717 "
Da min	7.8346 "
Da max	8.2677 "
Db min	8.4055 "
Ca min	0.2756 "
Cb min	0.3150 "
ra max	0.0787 "
r1a max	0.0787 "

Calculation factors

Equivalent dynamic radial load

$$P = X.F_r + Y.F_a$$

$F_a / F_r \leq e$		$F_a / F_r > e$	
X	Y	X	Y
1	0	0.4	Y2

Equivalent static radial load

$$P_0 = X_0.F_r + Y_0.F_a$$

X_0	Y_0
0.5	Y0

If $P_0 \leq F_r$, then use $P_0 = F_r$

The values for e, Y2 and Y0 are shown in the above table