

PDF technical sheet 32956XU



Single row tapered roller bearings

Tapered roller bearing, pressed steel cage

Product definition	
d	11.0236 "
D	14.9606 "
B	2.5000 "
C	1.8898 "
T	2.5000 "
d1	13.0512 "
a	2.9528 "
rs min	0.1181 "
r1s min	0.0984 "
e	0.43
Y2	1.39
Y0	0.76
Mass	70.55 oz
ISO 355 reference	T4EC280
Brand	NTN



Product performance	
Dynamic load, C	725 kN
Rating life coefficient, A2	1
Static load, C0	1,520 kN
Fatigue limit load, Cu	130 kN
Nlim (oil)	1,100 RPM
Nlim (grease)	790 RPM
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	248 °C
Characteristic cage frequency, FTF	0.47 Hz
Characteristic rolling element frequency, BSF	13.64 Hz
Characteristic outer ring frequency, BPF0	16.74 Hz
Characteristic inner ring frequency, BPFI	19.26 Hz



Abutment dimensions

da max	11.7323 "
db min	11.5748 "
Da min	13.5433 "
Da max	14.4882 "
Db min	14.4882 "
Ca min	0.4331 "
Cb min	0.5906 "
ra max	0.0984 "
r1a max	0.0787 "

Calculation factors

Equivalent dynamic radial load

$$P = X.F_r + Y.F_a$$

$F_a / F_r \leq e$		$F_a / F_r > e$	
X	Y	X	Y
1	0	0.4	Y2

Equivalent static radial load

$$P_0 = X_0.F_r + Y_0.F_a$$

X_0	Y_0
0.5	Y0

If $P_0 \leq F_r$, then use $P_0 = F_r$

The values for e, Y2 and Y0 are shown in the above table