

PDF technical sheet

4T32040XE1



Single row tapered roller bearings

Tapered roller bearing, pressed steel cage

Product definition	
d	7.8740 "
D	12.2047 "
B	2.7559 "
C	2.0866 "
T	2.7559 "
d1	10.0787 "
a	2.6181 "
rs min	0.1181 "
r1s min	0.0984 "
e	0.43
Y2	1.39
Y0	0.77
Mass	68.08 oz
ISO 355 reference	T4FD200
Brand	NTN



Product performance	
Dynamic load, C	800 kN
Rating life coefficient, A2	1.4
Static load, C0	1,470 kN
Fatigue limit load, Cu	135.30 kN
Nlim (oil)	1,400 RPM
Nlim (grease)	1,100 RPM
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	248 °C
Characteristic cage frequency, FTF	0.45 Hz
Characteristic rolling element frequency, BSF	9.49 Hz
Characteristic outer ring frequency, BPF0	12.60 Hz
Characteristic inner ring frequency, BPFI	15.41 Hz



Abutment dimensions

da max	8.7008 "
db min	8.4252 "
Da min	10.7480 "
Da max	11.7323 "
Db min	11.6929 "
Ca min	0.4331 "
Cb min	0.6693 "
ra max	0.0984 "
r1a max	0.0787 "

Calculation factors

Equivalent dynamic radial load

$$P = X.F_r + Y.F_a$$

Fa / Fr ≤ e		Fa / Fr > e	
X	Y	X	Y
1	0	0.4	Y2

Equivalent static radial load

$$P_0 = X_0.F_r + Y_0.F_a$$

X ₀	Y ₀
0.5	Y0

If $P_0 \leq F_r$, then use $P_0 = F_r$

The values for e, Y2 and Y0 are shown in the above table