

PDF technical sheet 4T32207CR




Single row tapered roller bearings

Tapered roller bearing, pressed steel cage

Product definition	
d	1.3780 "
D	2.8346 "
B	0.9055 "
C	0.7087 "
T	0.9547 "
a	0.8071 "
rs min	0.0591 "
r1s min	0.0591 "
e	0.58
Y2	1.03
Y0	0.57
Mass	1.63 oz
ISO 355 reference	T3DC035
Brand	NTN



Product performance	
Dynamic load, C	62 kN
Rating life coefficient, A2	1.4
Static load, C0	78.50 kN
Fatigue limit load, Cu	9.60 kN
Nlim (oil)	7,100 RPM
Nlim (grease)	5,300 RPM
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	248 °C



Abutment dimensions

da max	1.7126 "
db min	1.6535 "
Da max	2.5000 "
Db min	2.6772 "
ra max	0.0591 "
r1a max	0.0591 "

Calculation factors

Equivalent dynamic radial load

$$P = X.F_r + Y.F_a$$

$F_a / F_r \leq e$		$F_a / F_r > e$	
X	Y	X	Y
1	0	0.4	Y2

Equivalent static radial load

$$P_0 = X_0.F_r + Y_0.F_a$$

X_0	Y_0
0.5	Y0

If $P_0 < F_r$, then use $P_0 = F_r$

The values for e, Y2 and Y0 are shown in the above table