

PDF technical sheet 4T32224



Single row tapered roller bearings

Tapered roller bearing, pressed steel cage

Product definition	
d	4.7244 "
D	6.4961 "
B	1.1417 "
C	0.9055 "
T	1.1417 "
a	1.1614 "
rs min	0.0591 "
r1s min	0.0591 "
e	0.43
Y2	1.38
Y0	0.76
Mass	6.24 oz
ISO 355 reference	T4FD120
Brand	NTN



Product performance	
Dynamic load, C	162 kN
Rating life coefficient, A2	1.4
Static load, C0	294 kN
Nlim (oil)	2,600 RPM
Nlim (grease)	2,000 RPM
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	248 °C



Abutment dimensions

da max	5.0591 "
db min	5.0591 "
Da max	6.1614 "
Db min	6.2992 "
ra max	0.0591 "
r1a max	0.0591 "

Calculation factors

Equivalent dynamic radial load

$$P = X.F_r + Y.F_a$$

$F_a / F_r \leq e$		$F_a / F_r > e$	
X	Y	X	Y
1	0	0.4	Y2

Equivalent static radial load

$$P_0 = X_0.F_r + Y_0.F_a$$

X_0	Y_0
0.5	Y0

If $P_0 < F_r$, then use $P_0 = F_r$

The values for e, Y2 and Y0 are shown in the above table