

PDF technical sheet 4T32952XE1



Single row tapered roller bearings

Tapered roller bearing, pressed steel cage

Product definition	
d	10.2362 "
D	14.1732 "
B	2.5000 "
C	1.8898 "
T	2.5000 "
d1	12.2441 "
a	2.7362 "
rs min	0.1181 "
r1s min	0.0984 "
e	0.41
Y2	1.48
Y0	0.81
Mass	66.32 oz
ISO 355 reference	T3EC260
Brand	NTN



Product performance	
Dynamic load, C	705 kN
Rating life coefficient, A2	1.4
Static load, C0	1,430 kN
Fatigue limit load, Cu	124.10 kN
Nlim (oil)	1,100 RPM
Nlim (grease)	860 RPM
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	248 °C
Characteristic cage frequency, FTF	0.46 Hz
Characteristic rolling element frequency, BSF	12.81 Hz
Characteristic outer ring frequency, BPF0	15.73 Hz
Characteristic inner ring frequency, BPFI	18.27 Hz



Abutment dimensions

da max	10.9843 "
db min	10.7874 "
Da min	12.7953 "
Da max	13.7008 "
Db min	13.6614 "
Ca min	0.4331 "
Cb min	0.5906 "
ra max	0.0984 "
r1a max	0.0787 "

Calculation factors

Equivalent dynamic radial load

$$P = X.F_r + Y.F_a$$

$F_a / F_r \leq e$		$F_a / F_r > e$	
X	Y	X	Y
1	0	0.4	Y2

Equivalent static radial load

$$P_0 = X_0.F_r + Y_0.F_a$$

X_0	Y_0
0.5	Y0

If $P_0 \leq F_r$, then use $P_0 = F_r$

The values for e, Y2 and Y0 are shown in the above table