

PDF technical sheet 4TJH211749/JH211710




Single row tapered roller bearings

Tapered roller bearing, pressed steel cage


Product definition

d	2.5591 "
D	4.7244 "
B	1.5157 "
C	1.2598 "
T	1.5354 "
d1	3.5827 "
a	1.1063 "
e	0.34
Y2	1.78
Y0	0.98
Mass	6.70 oz
Brand	NTN



Product performance

Dynamic load, C	185 kN
Rating life coefficient, A2	1.4
Static load, C0	248 kN
Fatigue limit load, Cu	30.20 kN
Nlim (oil)	4,100 RPM
Nlim (grease)	3,100 RPM
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	248 °C
Characteristic cage frequency, FTF	0.43 Hz
Characteristic rolling element frequency, BSF	6.35 Hz
Characteristic outer ring frequency, BPF0	7.22 Hz
Characteristic inner ring frequency, BPFI	9.78 Hz



Abutment dimensions

ra max	0.1181 "
r1a max	0.0984 "

Calculation factors

Equivalent dynamic radial load

$$P = X.F_r + Y.F_a$$

$F_a / F_r \leq e$		$F_a / F_r > e$	
X	Y	X	Y
1	0	0.4	Y2

Equivalent static radial load

$$P_0 = X_0.F_r + Y_0.F_a$$

X_0	Y_0
0.5	Y0

If $P_0 < F_r$, then use $P_0 = F_r$

The values for e, Y2 and Y0 are shown in the above table