

PDF technical sheet

4TJLM714149/JLM714110PK



Single row tapered roller bearings

Tapered roller bearing, pressed steel cage


Product definition

d	2.9528 "
D	4.5276 "
B	0.9843 "
C	0.7480 "
T	0.9843 "
d1	3.7795 "
a	0.9961 "
e	0.46
Y2	1.31
Y0	0.72
Mass	3.09 oz
Brand	NTN



Product performance

Dynamic load, C	94.50 kN
Rating life coefficient, A2	1.4
Static load, C0	143 kN
Fatigue limit load, Cu	17.40 kN
Nlim (oil)	4,000 RPM
Nlim (grease)	3,000 RPM
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	248 °C
Characteristic cage frequency, FTF	0.45 Hz
Characteristic rolling element frequency, BSF	10.14 Hz
Characteristic outer ring frequency, BPF0	10.88 Hz
Characteristic inner ring frequency, BPFI	13.12 Hz



Abutment dimensions

ra max	0.1181 "
r1a max	0.0984 "

Calculation factors

Equivalent dynamic radial load

$$P = X.F_r + Y.F_a$$

$F_a / F_r \leq e$		$F_a / F_r > e$	
X	Y	X	Y
1	0	0.4	Y2

Equivalent static radial load

$$P_0 = X_0.F_r + Y_0.F_a$$

X_0	Y_0
0.5	Y0

If $P_0 < F_r$, then use $P_0 = F_r$

The values for e, Y2 and Y0 are shown in the above table