

PDF technical sheet

4TL327249



Single row tapered roller bearings

Mounted cone, sheet metal cage

Product definition	
d	5.2500 "
B	1.0313 "
d1	6.1417 "
e	0.35
Y2	1.72
Y0	0.95
Brand	NTN



Product performance	
Dynamic load, C	126 kN
Rating life coefficient, A2	1.4
Static load, C0	259 kN
Fatigue limit load, Cu	27.70 kN
Nlim (oil)	2,400 RPM
Nlim (grease)	1,800 RPM
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	248 °C
Characteristic cage frequency, FTF	0.47 Hz
Characteristic rolling element frequency, BSF	17.95 Hz
Characteristic outer ring frequency, BPF0	19.86 Hz
Characteristic inner ring frequency, BPFI	22.14 Hz



Abutment dimensions	
ra max	0.0591 "

Calculation factors

Equivalent dynamic radial load

$$P = X.F_r + Y.F_a$$

$F_a / F_r \leq e$		$F_a / F_r > e$	
X	Y	X	Y
1	0	0.4	Y2

Equivalent static radial load

$$P_0 = X_0.F_r + Y_0.F_a$$

X_0	Y_0
0.5	Y0

If $P_0 < F_r$, then use $P_0 = F_r$

The values for e, Y2 and Y0 are shown in the above table