

PDF technical sheet

32014.AP6X




Single row tapered roller bearings

Tapered roller bearing, pressed steel cage

Product definition	
d	2.7559 "
D	4.3307 "
B	0.9843 "
C	0.7480 "
T	0.9843 "
d1	3.5512 "
a	0.9370 "
rs min	0.0591 "
r1s min	0.0591 "
e	0.43
Y2	1.38
Y0	0.76
Mass	2.97 oz
ISO 355 reference	T4CC070
Brand	SNR



Product performance	
Dynamic load, C	104 kN
Rating life coefficient, A2	1
Static load, C0	160 kN
Fatigue limit load, Cu	19.50 kN
Nref	3,800 RPM
Nlim	6,200 RPM
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	248 °C
Characteristic cage frequency, FTF	0.45 Hz
Characteristic rolling element frequency, BSF	9.59 Hz
Characteristic outer ring frequency, BPF0	12.16 Hz
Characteristic inner ring frequency, BPFI	14.84 Hz



Abutment dimensions

da max	3.0709 "
db min	3.0906 "
Da min	3.8583 "
Da max	3.9961 "
Db min	4.1339 "
Ca min	0.1969 "
Cb min	0.2362 "
ra max	0.0591 "
r1a max	0.0591 "

Calculation factors

Equivalent dynamic radial load

$$P = X.F_r + Y.F_a$$

$F_a / F_r \leq e$		$F_a / F_r > e$	
X	Y	X	Y
1	0	0.4	Y2

Equivalent static radial load

$$P_0 = X_0.F_r + Y_0.F_a$$

X_0	Y_0
0.5	Y0

If $P_0 \leq F_r$, then use $P_0 = F_r$

The values for e, Y2 and Y0 are shown in the above table