

PDF technical sheet 32024A



Single row tapered roller bearings

Tapered roller bearing, pressed steel cage

Product definition	
d	4.7244 "
D	7.0866 "
B	1.4961 "
C	1.1417 "
T	1.4961 "
a	1.5591 "
rs min	0.0984 "
r1s min	0.0787 "
e	0.46
Y2	1.31
Y0	0.72
Mass	11.57 oz
ISO 355 reference	T4DC120
Brand	SNR



Product performance	
Dynamic load, C	250 kN
Rating life coefficient, A2	1
Static load, C0	420 kN
Fatigue limit load, Cu	45.40 kN
Nref	2,500 RPM
Nlim	3,700 RPM
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	248 °C



Abutment dimensions

da max	5.1575 "
db min	5.1969 "
Da min	6.3386 "
Da max	6.6929 "
Db min	6.8110 "
Ca min	0.2756 "
Cb min	0.3543 "
ra max	0.0787 "
r1a max	0.0787 "

Calculation factors

Equivalent dynamic radial load

$$P = X.F_r + Y.F_a$$

$F_a / F_r \leq e$		$F_a / F_r > e$	
X	Y	X	Y
1	0	0.4	Y2

Equivalent static radial load

$$P_0 = X_0.F_r + Y_0.F_a$$

X_0	Y_0
0.5	Y0

If $P_0 \leq F_r$, then use $P_0 = F_r$

The values for e, Y2 and Y0 are shown in the above table