

PDF technical sheet 33021A



Single row tapered roller bearings

Tapered roller bearing, pressed steel cage

Product definition	
d	4.1339 "
D	6.2992 "
B	1.6929 "
C	1.3386 "
T	1.6929 "
a	1.2205 "
rs min	0.0984 "
r1s min	0.0787 "
e	0.28
Y2	2.12
Y0	1.17
Mass	10.76 oz
ISO 355 reference	T2DE105
Brand	SNR



Product performance	
Dynamic load, C	265 kN
Rating life coefficient, A2	1
Static load, C0	450 kN
Fatigue limit load, Cu	50.50 kN
Nref	2,800 RPM
Nlim	4,200 RPM
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	248 °C



Abutment dimensions

da max	4.5669 "
db min	4.6063 "
Da min	5.7087 "
Da max	5.9055 "
Db min	6.0236 "
Ca min	0.2756 "
Cb min	0.3543 "
ra max	0.0787 "
r1a max	0.0787 "

Calculation factors

Equivalent dynamic radial load

$$P = X.F_r + Y.F_a$$

$F_a / F_r \leq e$		$F_a / F_r > e$	
X	Y	X	Y
1	0	0.4	Y2

Equivalent static radial load

$$P_0 = X_0.F_r + Y_0.F_a$$

X_0	Y_0
0.5	Y0

If $P_0 \leq F_r$, then use $P_0 = F_r$

The values for e, Y2 and Y0 are shown in the above table